

# NAVAL POSTGRADUATE SCHOOL

## Monterey, California



### BUCKLING OF SHIP GRILLAGES

by

D.A. Danielson  
D.P. Kihl

September 1996

Approved for public release; distribution is unlimited.


Prepared for: Naval Postgraduate School  
Monterey, CA 93943-5000

and

Naval Surface Warfare Center  
Carderock Division  
Washington, DC 20084-5000

19961104 056

# DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF COLOR PAGES WHICH DO NOT REPRODUCE LEGIBLY ON BLACK AND WHITE MICROFICHE.

NAVAL POSTGRADUATE SCHOOL  
Monterey, California

Rear Admiral M.J. Evans  
Superintendent

R. Elster  
Provost

This report was prepared for and funded by the Naval Postgraduate School and the Naval Surface Warfare Center, Carderock Division, Washington, DC.

Reproduction of all or part of this report is authorized.

The report was prepared by:




Donald Danielson  
Professor  
Department of Mathematics

Reviewed by:



Richard Franke  
Chairman  
Department of Mathematics

Released by:



David W. Netzer  
Associate Provost and Dean of Research

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)

September 1996

2. REPORT DATE

3. REPORT TYPE AND DATES COVERED

Technical Report October, 1995 - September 1996

4. TITLE AND SUBTITLE

BUCKLING OF SHIP GRILLAGES

5. FUNDING NUMBERS

N00167-96-WR-60226

6. AUTHOR(S)

D. A. Danielson  
D.P. Kihl

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Postgraduate School  
Code MA/Dd  
Monterey, CA 93943

Naval Surface Warfare  
Center  
Code 653  
Carderock Division  
Bethesda, MD 20084-5000

8. PERFORMING ORGANIZATION  
REPORT NUMBER

NPS-MA-96-002

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Naval Surface Warfare Center  
Carderock Division  
Washington, D.C. 20084-5000

Naval Postgraduate School  
Monterey, CA 93943

10. SPONSORING/MONITORING  
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

The views expressed in this report are those of the author and do not reflect the official policy or position of the Department of Defense or the US Government.

12a. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

The subject of this report is the mechanical behavior of stiffened plates, basic structural components of ships and submarines. The buckling loads of grillages subjected to axial compression with and without lateral pressure are calculated using a finite element based eigenvalue analysis. Insights are obtained into the ways in which the buckling loads and modes vary with various grillage dimensions.

14. SUBJECT TERMS

Ship Grillages, Plates, Buckling, Structures  
Finite Elements

15. NUMBER OF PAGES  
48

16. PRICE CODE

17. SECURITY CLASSIFICATION  
OF REPORT  
Unclassified

18. SECURITY CLASSIFICATION  
OF THIS PAGE

19. SECURITY CLASSIFICATION  
OF ABSTRACT

20. LIMITATION OF ABSTRACT  
Unclassified

# BUCKLING OF SHIP GRILLAGES

D. A. Danielson  
Code MA/Dd  
Naval Postgraduate School  
Monterey, CA 93943

D. P. Kihl  
Code 653  
Naval Surface Warfare Center, Carderock Division  
Bethesda, MD 20084-5000

September, 1996

## *ABSTRACT*

The subject of this report is the mechanical behavior of stiffened plates, basic structural components of ships and submarines. The buckling loads of grillages subjected to axial compression with and without lateral pressure are calculated using a finite element based eigenvalue analysis. Insights are obtained into the ways in which the buckling loads and modes vary with various grillage dimensions.

# CONTENTS

INTRODUCTION.....	1-3
EXPERIMENTALLY TESTED GRILLAGES.....	4-6
FIGURES 1 - 10 .....	7-16
GRILLAGES OF VARIOUS DIMENSIONS .....	17-21
FIGURES 11 - 34.....	22-45
CONCLUSIONS .....	46
REFERENCES .....	47

# INTRODUCTION

Stiffened plates are basic structural components of ships and submarines. These structures are designed with generous safety margins against overall collapse triggered by buckling. The object of mathematical modeling is to determine design criteria to inhibit buckling at any stress less than yield. In our earlier work (see References), we have reviewed the existing literature and developed new methods for predicting the buckling loads of simple plate-beam structures. In the present work, we calculate the axial buckling loads of grillages with the use of a well-known finite element code. The goal is to determine the effect on the buckling loads of varying various grillage parameters.

The grillage now modeled consists of 3 base plates with 4 longitudinal and 2 transverse stiffeners. The dimensions of this grillage are denoted in the report by

a1 = length between transverse stiffeners

a2 = length between transverse stiffener and grillage end

b1 = width between longitudinal stiffeners

b2 = width between outer longitudinal stiffener and grillage side =  $b1/3$

t1 = thickness of inner base plate

t2 = thickness of outer base plates =  $t1 \times \frac{4}{3}$

dw1 = depth of longitudinal webs

tw1 = thickness of longitudinal webs

df1 = depth of longitudinal flanges

tf1 = thickness of longitudinal flanges

dw2 = depth of transverse webs

tw2 = thickness of transverse webs

df2 = depth of transverse flanges

tf2 = thickness of transverse flange.

The material chosen for this study is isotropic steel with Young's modulus  $E = 3 \times 10^7$  psi and Poisson's ratio  $\nu = .3$ . The imposed boundary conditions are:

- (1) One end of the grillage has all 3 displacement components zero and all 3 rotation components zero.
- (2) The other end of the grillage where the force is applied has axial displacement constant with the other 2 displacement components zero and all 3 rotation components zero.
- (3) The ends of the transverse stiffeners have vertical displacement zero but the other 2 displacement components and all 3 rotation components are free.
- (4) All other nodes on the plates edges are completely free.

Because of the boundary conditions and the fact that the thickness  $t_2$  of the outer base plates is chosen to be  $\frac{4}{3}$  times the thickness  $t_1$  of the inner base plate, the buckling deflections of the outer bays are usually small compared to the buckling deflections of the central bay.

Thus we calculate the buckling stress in the *central* bay, defined as the initial end force divided by the cross-sectional area of the central bay, even though actual buckled members may be elsewhere.

The finite element code used is MSC Nastran/Patran. The pre-processing and post-processing is done with Patran (versions 1.4 and 1.5). The buckling analysis (solution 105) is done with Nastran (version 68). The base plates, flanges, and webs are each modeled with Quad 4 plate elements. The mesh size is denoted in this report by

$m_1$  = mesh length of all elements, mesh width of base plate elements

$m_2$  = mesh width of web and flange elements.

That is, the base plating has square elements of size  $m_1 \times m_1$ , while the webs and flanges have rectangular elements of size  $m_1 \times m_2$ . Note that this is a full finite element model of the entire grillage and does not assume symmetry. We use linear geometry for the axial load only cases, nonlinear geometry for the pressure cases, and linear material properties for all



cases. All computations are performed on a Silicon Graphics Indy Workstation.

The first phase of our work is to compare the finite element model with experimental results on a small scale grillage under axial and pressure loading. The second phase is to vary the dimensions on a full scale model to assess changes in buckling stress and mode under axial load only.

## EXPERIMENTALLY TESTED GRILLAGES

We first consider the grillages ( Figure 1) tested in the USNA Ship Structures Laboratory testing rig (Figure 2). We choose the following values for the model parameters:

$$a1 = 36''$$

$$a2 = 36''$$

$$b1 = 9''$$

$$t1 = \frac{3}{16}''$$

$$dw1 = 3''$$

$$tw1 = .114''$$

$$df1 = 1.844''$$

$$tf1 = .171''$$

$$dw2 = 9''$$

$$tw2 = .25''$$

$$df2 = 3''$$

$$tf2 = .25''$$

$$m1 = 1''$$

$$m2 = .5''.$$

We find that the buckling load is not significantly changed by adopting smaller values for the mesh sizes  $m1$  or  $m2$ .

The prebuckling stage is approximately one of uniform axial compression with little bending (Figure 3). The grillage buckles under a force of 470 kips. The buckling mode is a deformation involving primarily bending with little stretching (Figure 4). The inner base plate buckles into a square quilt of half-wavelength 9'' (Figure 5). The webs (both transverse and longitudinal) also buckle with half-wavelength 9'' (Figures 6-7). The flanges mainly just twist about their center line. We call this buckling mode TRIPPING to be consistent with

our earlier papers. \*

We also ran nonlinear analyses (solution 106) for the cases of bottom pressure  $p = 0$ ,  $p = 5$  psi, or  $p = 20$  psi. For the case  $p = 0$ , the plate only compresses in-plane and does not buckle. However, the buckles are clearly visible by the time the axial load reaches 475 kips for the  $p = 5$  psi case and 450 kips for the  $p = 20$  psi case. But since the buckling pattern develops gradually as the axial load increases, it is hard to pin down an exact "buckling" load. It is interesting that the middle plate develops only 3 half waves (instead of 4 as in the buckling analysis for  $p = 0$ ). The magnitude of displacement for the  $p = 20$  psi case is shown in Figure 8 with no axial load, and in Figure 9 with 550 kips axial load. If we increase the load much further than 500 - 550 kips, the displacements become large and the code will not give a solution (Figure 10).

A table comparing model results to experimentally measured collapse loads for 6 nominally identical grillages is given below:

p (psi)	Model (kips)	Experiments (kips)
0	470	326, 312, and 301
5	less than 475	316
10	not calculated	306
20	less than 450	296

---

\*In our earlier work, we did not allow the stiffener cross-section to deform in its plane. This assumption led to a predicted buckling load which was much too high.

Note that both theory and experiments indicate that the presence of lateral pressure (on the plating side) tends to weaken the grillages. The disparity between the buckling loads of the perfect model and the experimental measurements is probably due to geometric imperfections, residual stress, differing boundary conditions, nonlinear material properties, etc. in the tested grillages.





Figure 1



USNA Ship Structures Laboratory testing rig.

Figure 2

FRINGE PLOT LC=1.23 RES=2.1(VEC-MAG) MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 11:55:35  
 DEFORMATION PLOT LC=1.23 RES=2.1 MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 11:55:35

## Prebuckling magnitude of displacements




Figure 3

FRINGE PLOT LC=2.24 RES=3.1(VEC-MAG) MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:17:22  
 DEFORMATION PLOT LC=2.24 RES=3.1 MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:17:22

# 470 kips - Magnitude of displacement





Figure 4



FRINGE PLOT LC=2.24 RES=3.1(Z-COMP) MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:31:39  
 DEFORMATION PLOT LC=2.24 RES=3.1 MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:31:39

# 470 kips - z displacement



1.000  
 .8667  
 .7333  
 .6000  
 .4667  
 .3333  
 .2000  
 .06667  
 -.06667  
 -.2000  
 -.3333  
 -.4667  
 -.6000  
 -.7333  
 -.8667  
 -1.000

Figure 5

T-1C=2.24 RES=3.1(X-COMP) MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:40:05  
 S-2.24 RES=3.1 MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:40:05

# 470 kips - x displacement

.01497
.01290
.01083
.008754
.006682
.004610
.002538
.0004656
-.001607
-.003679
-.005751
-.007823
-.009895
-.01197
-.01404
-.01611




Figure 6

ST, LC=2.24 RES=3.1(Y-COMP) MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:46:30  
 ST, LC=2.24 RES=3.1 MSC/PATRAN R-1.4 MSC/NASTRAN 29-Jan-96 13:46:30

# 470 kips - y displacement

.1522	.1319	.1116	.09130	.07101	.05072	.03043	.01014	-.01014	-.03043	-.05072	-.07101	-.09130	-.1116	-.1319	-.1522
-------	-------	-------	--------	--------	--------	--------	--------	---------	---------	---------	---------	---------	--------	--------	--------





Figure 7

FRINGE PLOT LC=4.79 RES=2.1(VEC-MAG) MSC/PATRAN R-1.4 MSC/NASTRAN 12-Feb-96 10:18:49  
 DEFORMATION PLOT LC=4.79 RES=2.1 MSC/PATRAN R-1.4 MSC/NASTRAN 12-Feb-96 10:18:49

p=20 psi - Magnitude of displacement



.04989  
 .04657  
 .04324  
 .03991  
 .03659  
 .03326  
 .02994  
 .02661  
 .02328  
 .01996  
 .01663  
 .01330  
 .009979  
 .006652  
 .003326  
 .000000007000

Figure 8

FRINGE PLOT LC=3.90 RES=2.1(VEC-MAG) MSC/PATRAN R-1.4 MSC/NASTRAN 12-Feb-96 10:37:53  
 DEFORMATION PLOT LC=3.90 RES=2.1 MSC/PATRAN R-1.4 MSC/NASTRAN 12-Feb-96 10:37:53

p=20 psi, F=550 kips - Magnitude of displacement




Figure 9





Figure 10

# GRILLAGES OF VARIOUS DIMENSIONS

## Generic model

We define the generic model as a grillage with the following parameter values:

$$a1 = 96''$$

$$a2 = 48''$$

$$b1 = 24''$$

$$t1 = \frac{9}{16}''$$

$$dw1 = 6''$$

$$tw1 = .2''$$

$$df1 = 4''$$

$$tf1 = .225''$$

$$dw2 = 12''$$

$$tw2 = .2''$$

$$df2 = 4''$$

$$tf2 = .225''$$

$$m1 = 2''$$

$$m2 = 1''.$$

The buckling stress in the central bay of the generic model is 66.2 ksi. The buckling mode is TRIPPING of the central bay (Figure 11). The half-wavelength of the buckles is 24".

Note that the outer bays of the generic model are made half as long as the inner bay, to reduce the size of the finite element model. The buckling load of the full scale model differs from that of the generic model by an insignificant amount.

For the remainder of the report, we consider various grillages with only one dimension different from those of the generic model.

### **Variation of $a_1$ , length between transverse stiffeners**

We consider 6 grillages having differing values of  $a_1$ . All of the other parameters are the same as for the generic grillage, except for the case  $a_1 = 144''$  we choose the mesh length  $m_1 = 4''$  to make the program size smaller. The buckling stress decreases monotonically with  $a_1$  (Figure 12). The buckling mode is TRIPPING in all cases. For the 5 cases with  $a_1$  a multiple of 24", the half-wavelength of the buckles is 24". For the case  $a_1 = 60''$ , the half-wavelength is 30" (Figure 13).

### **Variation of $b_1$ , width between longitudinal stiffeners**

We consider 4 grillages having  $b_1$  differing multiples of 12". The buckling stress decreases monotonically with  $b_1$  (Figure 14). The buckling stress is somewhat larger than the classical buckling stress of a square simply-supported plate (Figure 15):

$$\frac{E\pi^2(t_1)^2}{3(1-\nu^2)(b_1)^2}$$

The buckling mode is TRIPPING (similar to Figure 11) and the half-wavelengths of the buckles is  $b_1$ .



## Variation of $t_1$ , thickness of inner base plate

We consider 5 grillages having differing values of  $t_1$ . The buckling stress reaches a maximum value for an optimal  $t_1$  (Figures 16 - 17). For the 3 lowest cases, the buckling mode is TRIPPING, with the half-wavelengths being 19.2" for the case  $t_1 = \frac{3}{16}$ " and 24" for the cases  $t_1 = \frac{3}{8}$ " and  $t_1 = \frac{9}{16}$ ". For the cases  $t_1 = \frac{3}{4}$ " and  $t_1 = \frac{15}{16}$ " the buckling mode is GLOBAL. The entire central bay buckles in (Figure 18), while the stiffeners deflect inwards and laterally (Figure 19).

## Variation of $dw_1$ , depth of longitudinal webs

We consider 7 grillages having differing values of  $dw_1$ . The buckling stress reaches a maximum value for an optimal  $dw_1$  (Figure 20). For the cases  $dw_1 = 3$ " and  $dw_1 = 4$ ", the buckling mode is GLOBAL (Figure 21). For the cases  $dw_1 = 5$ ",  $dw_1 = 6$ ", and  $dw_1 = 9$ ", the buckling mode is TRIPPING with half-wavelength of 24". For the cases  $dw_1 = 10$ " and  $dw_1 = 11$ ", the buckling mode is LOCAL (Figure 22). The web and flange of a middle stiffener of the central bay buckle with a half-wavelength  $dw_1$ . We find that the critical load for the local buckling case is not significantly changed by adopting smaller values for the web and flange mesh element width  $m_2$ .

## Variation of $tw_1$ , thickness of longitudinal webs

We consider 7 grillages having differing values of  $tw_1$ . The buckling stress increases monotonically with  $tw_1$  (Figure 23). For the case  $tw_1 = .05$ ", the web of a middle stiffener of the forward bay buckles LOCALLY, and for the case  $tw_1 = .1$ ", the web of a middle stiffener of the central bay buckles LOCALLY (Figure 24). For the cases  $tw_1 = .15$ ",  $.2$ ",  $.3$ ", and  $.7$ " the buckling mode is TRIPPING with half-wavelength 24" (Figure 25). For the case  $tw_1 = 1$ ", the buckling mode is TRIPPING with half-wavelength 19.2".

### **Variation of $df1$ , depth of longitudinal flanges**

We consider 4 grillages having differing values of  $df1$ . For the cases  $df1 = 2''$ ,  $4''$ , and  $6''$ , the buckling mode is TRIPPING and the buckling stress varies little (Figure 26). For the case  $df1 = 0$  (no flange), the web of a middle stiffener of the central bay buckles LOCALLY (Figure 27).

### **Variation of $tf1$ , thickness of longitudinal flanges**

We consider 4 grillages having different values of  $tf1$ . For the cases  $tf1 = .225''$ ,  $.5''$ , and  $1''$ , the buckling mode is TRIPPING and the buckling stress varies little (Figure 28). For the case  $tf1 = .1''$ , the flange of a middle stiffener of the central bay buckles LOCALLY (Figure 29).

### **Variation of $dw2$ , depth of transverse webs**

We consider 3 grillages having differing values of  $dw2$ . For all 3 cases  $dw2 = 4''$ ,  $12''$ , and  $16''$ , the buckling mode is TRIPPING and the buckling stress varies little (Figure 30).

### **Variation of $tw2$ , thickness of transverse webs**

We consider 3 grillages having differing values of  $tw2$ . For the cases  $tw2 = .15''$  and  $.2''$ , the buckling mode is TRIPPING and the buckling stress varies little (Figure 31). For the case  $tw2 = .1''$ , a web buckles LOCALLY under a *tensile* force (Figure 32). Compression in the web arises from Poisson ratio effects.

### **Variation of $df2$ , depth of transverse flanges**

We consider 2 grillages having differing values of  $df2$ . For both cases  $df2 = 0$  (no flange) and  $df2 = 4''$ , the buckling mode is TRIPPING and the buckling stress varies little (Figure 33). Note that eliminating the transverse flange would not reduce the buckling strength of the grillage under axial compression.

## Variation of $tf_2$ , thickness of transverse flanges

We consider 2 grillages having differing values of  $tf_2$ . For both cases  $tf_2 = .1''$  and  $tf_2 = .225''$ , the buckling mode is TRIPPING and the buckling stress varies little (Figure 34).

## Summary

Through study of all these different results, we can gain insights into the ways in which the buckling loads and modes vary with the various dimensions.

The buckling stress decreases less with length  $a_1$  than with width  $b_1$  between stiffeners. The buckling stress is larger for an optimal value of plating thickness  $t_1$  and depth  $dw_1$  of longitudinal webs. The buckling stress increases with thickness  $tw_1$  of longitudinal webs. The buckling stress is not much affected by increases in the dimension  $df_1$  and  $tf_1$  of the longitudinal flanges, dimensions  $dw_2$  and  $tw_2$  of transverse webs, or dimensions  $df_2$  and  $tf_2$  of transverse flanges. However, the buckling stress is smaller for too small values of thickness  $tw_1$  of longitudinal webs, depth  $df_1$  and thickness  $tf_1$  of longitudinal flanges, and thickness  $tw_2$  of transverse webs.

We have found three distinct failure modes which we have named TRIPPING, GLOBAL, and LOCAL. For the majority of our cases, the failure mode is TRIPPING with the inner base plate buckling into a square quilt, which forces the webs to buckle into a rectangular quilt with the same wavelength, while the flanges twist (Figure 11). However, if a square pattern cannot fit into the base plate (Figure 13), or if the relative strength of the stiffeners is much greater than the base plate (Figure 25), the inner base plate may buckle into a non-square quilt, and the flanges may also undergo lateral deformation. If the relative strength of the inner base plate is much greater than the stiffeners, the failure mode may be GLOBAL with the entire central bay buckling in (Figures 18-19 and 21). If the relative strength of a stiffener is too small, it may collapse LOCALLY before any of the other components buckle (Figures 22, 24, 27, 29, and 32).




Figure 11

Buckling stress in central bay - ksi




Figure 12

DEFORMATION PL4-93T




Figure 13

Buckling stress in central bay - ksi




Figure 14





Figure 15






Figure 16




Figure 17

FRINGE PLOT LC=2.2 RES=3.1(Z-COMP) MSC/PATRAN R-1.4 MSC/NASTRAN 18-Mar-96 13:09:09  
 DEFORMATION PLOT LC=2.2 RES=3.1 MSC/PATRAN R-1.4 MSC/NASTRAN 18-Mar-96 13:09:09

t1=.9375", 74.1 ksi, z-displacement

.009002

.002885

-.003233

-.009350

-.01547

-.02158

-.02770

-.03382

-.03994

-.04605

-.05217

-.05829

-.06441

-.07052

-.07664

-.08276




Figure 18

FRINGE PLOT LC=2.2 RES=3.1(Y-COMP) MSC/PATRAN R-1.4 MSC/NASTRAN 18-Mar-96 13:24:48  
 DEFORMATION PLOT LC=2.2 RES=3.1 MSC/PATRAN R-1.4 MSC/NASTRAN 18-Mar-96 13:24:48

t1=.9375", 74.1 ksi, y-displacement




Figure 19




Figure 20

FRINGE PLOT LC-2.2 RES=3.1(VEC-MAG) MSC/PATRAN R-1.4 MSC/NASTRAN 01-Apr-96 10:33:06  
 DEFORMATION PLOT LC-2.2 RES=3.1 MSC/PATRAN R-1.4 MSC/NASTRAN 01-Apr-96 10:33:06

.1890

dw1=4", 51.5 ksi, Magnitude of displacement

.1638

.1512

.1386

.1260

.1134

.1008

.08821

.07560

.06300

.05040

.03780

.02520

.01260

.00000004100




Figure 21




Figure 22




Figure 23






Figure 24




Figure 25




Figure 26

FRINGE PLOT LC=2.2 RES=3.1 (VEG-MAG) MSG/PATRAN R-5.0 MSC/NASTRAN 02-JUL-96 12:28:02  
 DEFORMATION PLOT LC=2.2 RES=3.1 MSC/PATRAN R-5.0 MSC/NASTRAN 02-JUL-96 12:28:02

df1=0, 30.8 ksi, Magnitude of displacement




Figure 27




Figure 28




Figure 29




Figure 30




Figure 31






Figure 32




Figure 33




Figure 34

## CONCLUSIONS

We can think of the buckling stress as being represented by a surface in  $n$ -dimensional parameter space ( $n = 11$  in our studies). The surface is continuous but has discontinuous slope at the boundaries between subsurfaces corresponding to TRIPPING, GLOBAL, or LOCAL modes. Our curves of buckling stress versus a parameter are the intersections of the surface with vertical planes passing through a given point on the surface.

To fit the entire surface with an analytical approximation would appear to be a difficult computational problem requiring the calculation of numerous points on the surface. The parameter dependence of the buckling load is coupled, i.e., all the parameters would have to be varied simultaneously.

In future work the finite element eigenvalue code could be used to design the ideal structure. One possible design criterion would be to find the grillage of minimum weight among all possible grillages with buckling stress equal to the yield stress. The candidate points would lie on the intersection of the surface with a horizontal plane.

## ACKNOWLEDGEMENTS

The authors were supported by the Naval Surface Warfare Center, Carderock Division, and by the Naval Postgraduate School Research Program.

## REFERENCES

- Danielson, D. A., and Hodges, D. H. (1988). A beam theory for large global rotation, moderate local rotation, and small strain. *ASME Journal of Applied Mechanics* 55, 179-184.
- Danielson, D. A., Kihl, D. P., and Hodges, D. H. (1990). Tripping of thin-walled plating stiffeners in axial compression. *Thin-Walled Structures* 10, 121-142.
- Danielson, D. A., Cricelli, A. S., Frenzen, C. L. and Vasudevan, N. (1993). Buckling of stiffened plates under axial compression and lateral pressure. *International Journal of Solids and Structures* 30, 545-551.
- Danielson, D. A., (1994). Analytical tripping loads for stiffened plates. *International Journal of Solids and Structures*. 32, 1319 - 1328.
- Danielson, D. A., Steele, C. R., Fakhroo, F. and Cricelli, A. S. (1994). Stresses in Ship Plating. *Naval Postgraduate School Technical Report* NPS-94-008.

## Distribution List

	No. of copies
Director Defense Technology Information Center Cameron Station Alexandria, VA 22314	2
Director of Research Administration Code 81 Naval Postgraduate School Monterey, CA 93943	1
Library Code 52 Naval Postgraduate School Monterey, CA 93943	2
Chairman, Code MA Department of Mathematics Naval Postgraduate School Monterey, CA 93943	2
Professor D. A. Danielson Code MA/Dd Naval Postgraduate School Monterey, CA 93943	30
Dr. Marc Lipman Mathematical, Computer and Information Sciences Division Office of Naval Research 800 Quincy Street Arlington, VA 22217-5000	1
Dr. David Kihl Survivability, Structures, and Materials Directorate Naval Surface Warfare Center-Carderock Division Bethesda, MD 20084-5000	5